

ŠROUBOVÁKY

PRŮMYSLOVÉ PŘÍJEMNÍ

ZT-31
digitální měřič momentu
rozsah 0-10 Nm



RA-3011 / RA-3017 / RA-3023
RA-4008 / RA-4015 / RA-4021
RA-5005 / RA-5008 / RA-5017



	Upínací šestíhran mm	Rozsah momentu Nm	Otáčky na prázdno min ⁻¹	Průměrná spotřeba vzduchu l/min	Pracovní tlak bar	Celková délka mm	Hmotnost kg	Hadice mm	Hlučnost dle EN ISO 15744 dB(A)	Vibrace m/s ²
RA - 3011	6.35	1.1-2.1	1100	198	6.3	187	0.42	8	70.0	2.0
RA - 3017	6.35	0.7-1.5	1700	198	6.3	187	0.42	8	70.0	2.0
RA - 3023	6.35	0.4-1.0	2300	198	6.3	187	0.42	8	70.0	2.0
RA - 4008	6.35	1.6-4.0	800	297	6.3	209	0.65	8	74.0	2.5
RA - 4015	6.35	1.0-2.2	1500	297	6.3	209	0.65	8	74.0	2.5
RA - 4021	6.35	1.0-1.7	2100	297	6.3	209	0.65	8	74.0	2.5
RA - 5005	6.35	5.0-10.5	480	495	6.3	240	1.0	10	75.0	10
RA - 5008	6.35	3.0-5.5	800	495	6.3	240	1.0	10	75.0	10
RA - 5017	6.35	1.5-2.6	1700	495	6.3	240	1.0	10	75.0	10